

## Guardian Mobile Device Specifications (1-way video)

### Physical Dimensions:

Base Footprint: 31" x 34"

Weight: 51.8 lbs.

Height: 78"

Construction: Cast and extruded aluminum  
steel and molded ABS/PVC thermoplastic

### Power Specifications:

Input: 90-264 VAC, 50/60Hz

Max Current Draw: 975 mA

Typical Current Draw: 500 mA

Cable Length: 10 ft. NEMA 5-15P to IEC 60320 C13

*Replacement or Non-standard length cords available for purchase*

Contact [info@avasure.com](mailto:info@avasure.com) for a quote

### Mobile Device Certification:

File E479999

UL 60950-1, 2nd Edition + Amendment 1 + Amendment 2,  
2019-05-09 (Information Technology Equipment - Safety - Part  
1: General Requirements)

CAN/CSA C22.2 No. 60950-1-07, 2nd Edition + Amendment 1  
+ Amendment 2, 2014-10-14 (Information Technology  
Equipment - Safety - Part 1: General Requirements)

UL CERTIFICATE OF COMPLIANCE 20200318-E479999

FCC Title 47 CFR Part 15

### Operating Conditions:

0 – 46 °C (32 – 115 °F)

### Per Device Bandwidth Requirements:

Average: 768 Mbps

Average with Infrared: 1.2 Mbps

Peak with full range PTZ: 3.0 Mbps

### Camera Resolution:

1920x1080 to 320x180; 1280x720 Typical

### Audio System:

Microphone element sensitivity –38dB +/- 3db

Frequency response 90Hz – 8.3kHz

Speaker power output 10 W

Two-way, half duplex (default), full duplex

Additional installation documentation provided during Project Planning phase.

**⚠ WARNING:** These products contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information:  
<http://www.P65warnings.ca.gov/>

